

MSR Gold™ MiniFastFit (Touring/Stage)

MSR Gold™ 1000 MiniFastFit

Thanks to the specially designed lamp base, the MSR Gold™ MiniFastFit takes just seconds to replace, to help ensure non-stop clubbing entertainment. In addition, the innovative gold plated pins ensure excellent current transfer to prolong lamp and lamp holder lifetimes and thereby reduce lamp replacement costs. Easy handling and small compact fixture designs are allowed by the lamps compact size, while the very short arc provides a high perceived brightness and high beam intensity.


Product data

• General Characteristic	S	Dimmable	No			
System Description Cap-Base Cap-Base Information Execution Operating Position Main Application Life to 50% failures	MiniFastFit PGJX36 PGJX36 - any Entertainment 900 hr	 Luminaire Design Requires Pinch Temperature Bulb Temperature Product Dimensions 	irements 500 (max) C 950 (max) C			
EM		Overall Length C Diameter D	112 (max) mm 26 (max) mm			
• Light Technical Charac	teristics	Width F	35.3 (min), 36 (nom), 36.5 (max) mm			
Color Code Color Rendering Index	- 80 Ra8	Light Center Length L Arc Length O	55 (min), 56 (nom), 57 (max) mm 5.5 mm			
Color Temperature Color Temperature	6000 K 6000 K	• Product Data				
Technical Chromaticity Coor- dinate X	0.321 -	Order code Full product code	928171405115 928171405115 MSR Gold™ 1000 MiniFastFit MSR Gold 1000 MiniFastFit 1 4 4 8718291785088			
Chromaticity Coor- dinate Y	0.330 -	Full product name Order product name				
Luminous Flux Lamp EM	74000 (min), 82000 (nom) Lm	Pieces per pack Packing configuration				
Luminous Efficacy Lamp EM	82 Lm/W	Packs per outerbox Bar code on pack - EAN1				
• Electrical Characteristi	cs	Bar code on outerbox - EAN3	8718291785095			
Lamp Wattage	1000 W	Logistic code(s) -	928171405115			

12NC

Net weight per piece


0.055 kg






MSR Gold[™] MiniFastFit (Touring/Stage)

Dimensional drawing



MSR Gold™ 1000 MiniFastFit

Product	A (Min)	A (Norm)	A (Max)	C (Max)	D (Max)	D1 (Norm)	F (Min)	F (Norm)	F (Max)	L (Min)	L (Norm)	L (Max)	O (Norm)
MSR GOLD 1000 MiniFastFit	-	-	-	112	26	-	35.3	36	36.5	55	56	57	5.5



PGJX36



© 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting