



DOUBLE SIDED EXHIBITION TAPE

18350 double sided cloth exhibition tape is designed for bonding with removability functions. This tape can be used on almost every type of flooring, such as hard wood surfaces, stone, etc.

Construction

| | |
|-----------------|---|
| Adhesive | Synthetic rubber (open side); Synthetic rubber (covered side) Very high tack |
| Carrier | Fabric Transparent |
| Liner | Siliconized paper Brown |

Applications

Especially designed for temporary fixing of floorcoverings during fairs & events.
Suitable for almost all kinds of surfaces and most types of carpets.
Cleanly removable on most surfaces.

Technical details

| | |
|----------------------------------|---|
| Thickness | 0,23 mm |
| Adhesive strength | 10 N/25 mm (open side); 20 N/25 mm (covered side) |
| Service temperature range | -10°C to +75°C |
| Humidity resistance | Good |
| Ageing resistance | Good |

Recommendations for use

Temperature: between +10°C and +30°C. Surface must be clean and free from dust and grease. Avoid touching exposed adhesive surface of the tape, as this impairs the performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24HRS at +23°C.

Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature between +10°C and +30°C. Stored under these conditions shelf life will be a minimum of 12 months.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Option Tape Specialties cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.



OPTION TAPE SPECIALTIES

Frankrijkstraat 8
9140 Temse - Belgium
Tel. : +32 (0)3 710 19 19 - Fax : +32 (0)3 711 34 64
info@optiontapespecialties.com - www.optiontapespecialties.com