


## NOCTIS LUX 3 10W floodlight




CE

Power	<b>10 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>950 lm (120°)</b>	Colour of light	<b>WW</b>
Beam angle	<b>100 °</b>	IK	<b>07</b>
Degree of protection (IP)	<b>IP65</b>		



See more on dedicated page 



 Declaration of Conformity



 Photometric file

**Technical data:**

Code	SLI029052WW_PW
Power	10 W
Nominal current	45 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	10 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	950 lm (120°)
Luminous flux**	950 lm (360°)
Lamp efficacy	95 lm/W
Colour of light	WW
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	90x75x27 mm
Weight	0.159 kg
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux