

**Product code: P7110028**
**SQUARE IP 300W 6in1 RGBWA+UV IP65**


TECHNICAL DATA	
Power consumption	300W
Power supply voltage	100 - 245V
Voltage frequency	50/60Hz
Diode type	COB 6in1
Number of diodes	1
Diode power	300W
Display	Color LCD 1,8"
UTILITY DATA	
Color	RGBWA + UV
Luminous flux	26 800 lm
Color rendering index (CRI)	87
Beam angle (min)	37°
Beam angle (max)	37°
Dimming	Linear: 0 - 100%
DMX Standard	DMX 512
Control interface	4 buttons
Operating modes	DMX512, Auto, Master / Slave, Manual
INTERFACES	
AC IN	dedicated IP65 power plug
AC OUT	dedicated IP65 power plug
DMX IN	XLR - 3 pin, XLR - 5 pin
DMX OUT	XLR - 3 pin, XLR - 5 pin
PHYSICAL CHARACTERISTIC	
IP Rating	IP65
Cooling	Active
Housing made	Aluminium + Steel
Height [cm]	24
Width [cm]	25,7
Depth [cm]	16
Packing size [cm]	38x35x17
Weight [kg]	5,8
Weight with packaging [kg]	6,8
Type of packaging	Carton Box