


SLI044017NW




Power	100 W	Voltage	230 V
Luminous flux*	14700 lm (120°)	Colour of light	NW
Beam angle	90 °	UGR	n/a lm
IK	10	Degree of protection (IP)	IP66



 User manual




 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI044017NW
Power	100 W
Nominal current	436 mA
Voltage	230 V
Energy efficiency class	C
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.95
Luminous flux*	14700 lm (120°)
Luminous flux**	17000 lm (360°)
Lamp efficacy	170 lm/W
Luminous intensity	8100 cd
Colour of light	NW
Beam angle	90 °
UGR	n/a
RA	>80
Light source included	Yes
Dimmable	1-10V
Working temperature range	-20 +40 °
Lifespan	50000 h
Housing material	Aluminum
IK	10
Degree of protection (IP)	IP66
Colour	Black
Dimension (AxBxC)	263x110 mm
Weight	2.52 kg
For use	Inside/Outside
Assembly	Suspended
Whether it should work in conditions other than normal	Yes
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux