

## SLI029046CW PW



CE

---

Power	<b>100 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>9400 lm (120°)</b>	Colour of light	<b>CW</b>
Beam angle	<b>100 °</b>	IK	<b>07</b>
Degree of protection (IP)	<b>IP65</b>		

---



 Photometric file

Technical data:

Code	SLI029046CW_PW
Power	100 W
Nominal current	435 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	9400 lm (120°)
Luminous flux**	9400 lm (360°)
Lamp efficacy	94 lm/W
Colour of light	CW
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	270x210x27 mm
Weight	1.256 kg
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux