


**SWATCHBOOK:** ROSCOLUX  
**COLOR FILTER:** #50 MAUVE  
**DESCRIPTION:** Color Effects Lighting Filter.  
**TRANSMISSION =** 14% or -2.8 stop loss  
**MIREID SHIFT =** Not Applicable.  
**CC EQUIVALENT =** Not Applicable.

**COLORIMETRIC DATA**

**OBSERVER:** CIE 1964 10°  
**SOURCE:** • 'A' (tungsten)  
           ° 'D65' (daylight)




HUNTER LAB SOURCE A	
L*	44.879
A*	42.630
B*	19.283

HUNTER LAB SOURCE D65	
L*	39.188
A*	41.001
B*	6.533

CIE 1964 SOURCE A	
Y	14.465
(x)	0.591
(y)	0.343

CIE 1964 SOURCE D65	
Y	10.769
(x)	0.449
(y)	0.293



nm.	360	380	400	420	440	460	480	500	520	540	560	580	600	620	640	660	680	700	720	740
trans %	15	32	34	18	9	6	5	5	6	6	6	9	16	31	53	70	79	83	84	85

**MATERIAL SPECIFICATIONS:**

**General Description:** Co-extruded Polycarbonate Film  
**Substrate:** PC (Polycarbonate)  
**Thickness:** 3.0 mil (.003" or 76.2 micron)  
  
**Manufactured in:** U.S.A.

**AVAILABLE SIZES:**

- ✓ 20 in. x 24 in. sheets (50cm x 60cm)
- ✓ 24 in. x 25 ft. rolls (60cm x 7.62m)
- 48 in. x 25 ft. rolls (121cm x 7.62m)
- 60 in. x 20 ft. rolls (152.4cm x 6.10m)
- 13.5 in. Diameter Glass (34.3cm) - Cut to order